



POLYFLEX TILE ADHESIVE

An acrylic based tile adhesive for PVC tiles

Description:

This is an acrylic based tile adhesive which is highly recommended for PolyflexFloor Tiles/ Polyflor XL Pu. It is a thick creamy Acrylic based compound specifically designed to bond Polyflex PVC Floor Tiles to concrete and wooden surfaces.

It may also be used for bonding Wooden Parquets to floors, expanded polystyrene to ceilings and walls, fiberglass insulations to walls.

Typical Properties:

Open and working times depend on temperature, relative humidity and substrate absorbency. These times decrease with increasing temperature and decreasing relative humidity. The opposite climatic conditions and non-absorbent substrate cause a lengthening of these times.

Caution:

Ensure the working surface is smooth, clean, dry, free from dust, grease polish or other foreign matter. For new concrete floors and plaster, allow sufficient time to dry out before the adhesive is applied. No evidence of rising damp should be present.

Storage:

Store in a cool dark place, not subject to direct sunlight.

Equipment care:

Clean all tools used immediately when wet.

Application:

- Stir well before use.
- Surface should be clean, free of grease, oil, dust or any loose material.
- Apply Polyflex Adhesive with a notched trowel (notches 1.5mm triangular at 5mm centers).
- Allow adhesive film to dry until it changes color from white to transparent.
- Place the tiles as required on the film.
- Wipe off the excess adhesive with a cloth.

Coverage:

Approximately 3.5 sq.m per Kg depending on the surface it is applied on.

Safety Precautions:

A non-flammable, yet it can burn slowly if the surface is dry. Use protective clothing and eye wear when handling the product, if in contact with skin or eyes, wash with clean water.

Note:

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KENBRO INDUSTRIES LTD representative.

KENBRO INDUSTRIES LTD reserves the right to have the true cause of any difficulty determined by accepted test methods.

KENBRO INDUSTRIES LTD

HEAD OFFICE:

Corner of Wambugu Road and Limuru Road

T - (020) 242 2242/3 | (020) 243 3383/5

M- 0724 255 674 | 0735 633 199

KENBRO INDUSTRIES LTD

FACTORY:

Off Mombasa Road

T - (020) 354 7945/6/7 | (020) 3535463

M - 0722 848585 | 0733697959